NECTRA LED IP44 9W 4000K WHITE



OFFICE LIGHTING









CHARACTERISTIC

059933 Index: 230V Supply voltage: Frequency: 50Hz Ingress protection IP: IP44 Rated power: 9W Energy efficiency class: A + Ш Electrical protection class:

Mounting dimensions : ø100mm 4000K Colour temperature : 710lm Luminous flux *:

SPECIFICATION

Downlight type fitting with an integrated energy-saving LED source. Made of lightweight aluminium and plastic.

Its distinctive features are low profile, light weight and very easy and fast installation. Design for both solid and modular ceilings.


APPLICATION

Designed for indoor use in common areas, passageways or to provide additional illumination in the office rooms.

Due to equal surface illumination and high energy savings, it is especially recommended for public buildings.

LUMINOUS INTENSITY DISTRIB. CURVE

NECTRA LED IP44 9W 4000K WHITE





^{*} Initial, tolerance +/- 10%

NECTRA LED IP44 9W 4000K WHITE



OFFICE LIGHTING

Index:	059933
Supply voltage:	230V
Frequency:	50Hz
Ingress protection IP:	IP44
Impact resistance IK:	IK08
Rated power:	9W
Luminous efficacy:	79lm/W
Energy efficiency class:	A +
Electrical protection class:	II
Mounting dimensions:	ø100mm
Net weight of 1 unit:	0,18kg
Material of the body:	PC, Aluminium
Colour temperature:	4000K
Luminous flux*:	710lm
(EAN) European Article Number:	5905963059933
Material of the diffuser:	PMMA
Type of the diffuser:	Opal
Light source:	LED

^{*} Initial, tolerance +/- 10%




NECTRA LED IP44 9W 4000K WHITE



OFFICE LIGHTING

TECHNICAL DRAWINGS



A=121 B=67

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2016-02-15







